




POWER OFFICE SERIES FEATURES

- 800 VA ~ 950 VA line interactive UPS
- 3 LEDs indicates UPS statuses, including normal, charging, back-up, battery low, fault, and overload
- Advanced battery management to increase battery longevity, performance and reliability
- Two boost and one buck automatic voltage regulator for high and low voltage
- DC cold start function for greater mobility
- Auto restart while AC is recovering
- 2 USB charging ports for USB devices
- RJ-11 / 45 combo telephone / fax / network line protection port
- Off-mode charging
- USB communication port with power management software to control & monitor UPS status (CSA models)
- Coaxial surge protection (Optional for CSA models)

Socket type



APPLICATIONS

- PC / Gaming Computers
- P.O.S.
- Surveillance & Security
- A / V & Home Theater



POWER OFFICE LINE INTERACTIVE UPS SPECIFICATION

MODEL	POF-800AU	POF-950AU	POF-800CSA	POF-950CSA
Capacity	800 VA / 420 W	950 VA / 500 W	800 VA / 420 W	950 VA / 500 W
INPUT				
Voltage	220 / 230 / 240 VAC			
Voltage Range	-30% ~ +25%			
Frequency	50 / 60 Hz (auto sensing)			
OUTPUT				
Voltage	220 / 230 / 240 VAC			
Voltage Regulation (Battery Mode)	±10%			
Frequency	50 / 60 Hz			
Frequency Regulation (Battery Mode)	±1 Hz			
Waveform (Battery Mode)	Simulated sine wave			
Typical Transfer Time	2 ~ 6ms (typical)			
Outlets	6 UK or 6 Schuko or 6 Australia (3 backup&surge + 3 surge only) or 9 Thailand (5 backup&surge + 4 surge only)			
BATTERY				
Battery Type & Quantity	12 V / 7 Ah x 1	12 V / 9 Ah x 1	12 V / 7 Ah x 1	12 V / 9 Ah x 1
Backup Time (Basic PC)	Up to 20 minutes	Up to 30 minutes	Up to 20 minutes	Up to 30 minutes
Typical Recharge Time	< 5 Hours to 90% capacity			
PROTECTION				
Full Protection	Over discharge protection & short circuit protection			
Tel / Fax / Network Suppression	RJ-11 / 45 combo port			
Lighting & Surge Protection	175 Joules		480 Joules	
Coaxial Protection	N / A		Optional	
USB				
Charging Interface (2 Ports)	5 VDC / 2.1Amp (max.) charge current			
Monitoring Software	N / A		Communication software for windows® 2000 / 2003 / XP / Vista / 2008 / 7 / 8 / 10	
PHYSICAL				
Dimension (D x W x H) (mm / in)	290 x 94 x 170 / 11.4 x 3.7 x 6.7			
Net Weight (kg / lb)	5 / 11.0	5.9 / 13.0	5 / 11.0	5.9 / 13.0